



AIR-COOLED PISTOL GRIP

For use with difficult-to-feed wires such as Aluminum and/or other specialty applications. Available in 238,307,347,407 and 507 model torches




EXTENDED TRIGGER OPTION

For increased personal welder comfort. Manufactured from Heavy-Duty Aluminum. Ensures durability and resists breaking as compared to plastic triggers.

DUAL/MULTI-SCHEDULE OPTION

The Dual Schedule allows the operator to change between two weld schedules. The Multi-Schedule is a momentary switch and can be used to increase or decrease through numerous preset weld schedules. Both options can be used to change schedules "on the fly".



QUICK CHANGE GOOSENECK

Allows for fast and easy change-out of goosenecks for repair or torch reconfiguration. Six selectable positions available for



GUN HANGER

HEAT
SHIELD



GOOSENECK

THERMAL SPRING



TORCH RATINGS

MODEL	AMPERAGE	100% DUTY CYCLE			60% DUTY CYCLE		
		CO2	Mixed Gas(AG/CO2)	Pulsed/High Dep. Wire, Ar/O Mix	CO2	Mixed Gas(AG/CO2)	Pulsed/High Dep. Wire, Ar/O Mix
238CA	260	260A	210A	150A	300A	260A	200A
347CA	300	300A	275A	200A	350A	325A	275A
407CA	400	400A	325A	225A	450A	400A	325A
507CA	500	500A	400A	325A	525A	500A	400A

TORCH STANDARD CONFIGURATION CHART

GUN SERIES	STD TIP SIZE	TIP PART #	DIFFUSER	NOZZLE BORE SIZE	NOZZLE PART #	STD. FEEDER CONNECTION	GOOSENECK ANGLE
238CA/PG	.035(0.9mm)-M6	75035511	75002007	9/16"(15.1mm)	75135601-I	Euro	60°
347CA/PG	.045(1.2mm)-M6	75045511	75002007	5/8"(15.9mm)	75146204-I	Euro	60°
407CA/PG	.045(1.2mm)-M8	75045014	75004033	5/8"(15.9mm)	75146202	Euro	60°
507CA/PG	.045(1.2mm)-M8	75045014	75004033	5/8"(15.9mm)	75157501	Euro	60°

HOW TO ORDER

407CA
GUN SERIES
CA - STANDARD
PG - PISTOL GRIP

15
LENGTH

.T5
WIRE FEEDER
PLUG

-ET
OPTIONS

** Specify wire size and or special configuration when ordering if not standard

OPTIONS

ET - Extended Trigger
DS - Dual Schedule Switch
ID - Increase/Decrease Switch
TS - Thermal Spring
GL - Gasless Consumables
QC - Quick Change Gooseneck
GUN HANGER - 75000009 (Must be ordered separately)
HEAT SHIELD - 75000030 (Must be ordered separately)

WIRE FEEDER CONNECTION OPTIONS

B - EURO
C - CENTURY/TOWSON®
CL - CLOOS®
D - OTC®/DAIHEN®
DP - OTC®/DAIHEN® DP SERIES

H5 - HOBART® #5
K - KODOLCO®
L - LINCOLN® (LN7 STYLE)
LT - L-TEC® 225
M - MILLER®
O - OXO®

P - PANASONIC®
T - TWECO®/HOBART® #4
TL - LINCOLN® POWER FEED 10
T5 - TWECO® #5
W - LINCOLN® WIREMATIC